

LNE-DGJ-M 黄铜自固式接头 Brass Circlip Self Secured Fitting



产品材质: B,D,G部位采用优质黄铜镀镍, C,F部位采用丁腈橡胶制成, E为铁皮压铸制成。
工作温度: -40℃至+100℃,短时可达+120℃。
产品特性: 1.优质黄铜镀镍、外型美观、结构紧密、强度高。
2.软管护套设计与软管相扣接紧之设计、装配省时便利, 抗拉力强。
3.可防水、防尘、抗盐、耐酸碱、酒精、油、脂及一般溶剂。
除以下标准规格外, 可另按要求任意变动大小。

Product material: B,D,G are made of nickel-plated brass, C and F are made of chemigums, E is made of iron.

Working temperature: -40°C ~ +100°C, instantaneously can be +120°C

Property:

1. nickel-plated brass, nice looking, compact structure and high strength.
2. Ferrule design make conduit connection tightly, easy assembly, and strong pull resistance.
3. Water resistant, dust resistant, inactive with salts, acid and alkali resistance, alcohols, oils and greases as well as general solvent.

Besides the following specifications, the size and thread standard can be varied at your discretion as per requirements.

订货号 Order No.	配套金属软管(公制) Matching metal Hose(M)	螺牙厚钢管 Threaded Thick Steel Conduit		薄钢管 Thin Steel Conduit		扳手尺寸(mm) Wrench	包装单位(只/包) Packaging Unit
		公制 M	外径X壁厚 (mm) Outer Diameter x Wall Thickness	公制 M	外径X壁厚 (mm) Outer Diameter x Wall Thickness		
No.	Φ	M	OxW	M	OxW	SW	PCS
LNE-DGJ-M-10	Φ10	#10		#12	12.76 × 1.60	24	100
LNE-DGJ-M-12	Φ12(13)	#12	17.00 × 2.25	#15	15.87 × 1.60	26	100
LNE-DGJ-M-16	Φ15(16)	#15	21.25 × 2.75	#20	19.05 × 1.80	28	50
LNE-DGJ-M-20	Φ20(19)	#20	26.75 × 2.75	#25	25.40 × 1.80	35	50
LNE-DGJ-M-25	Φ25	#25	33.50 × 3.25	#32	31.75 × 1.80	42	50
LNE-DGJ-M-32	Φ32	#32	42.25 × 3.25	#40	38.10 × 1.80	50	20
LNE-DGJ-M-38	Φ38(40)	#40	48.00 × 3.50	#50	50.80 × 2.00	57	20
LNE-DGJ-M-51	Φ51(50)	#50	60.00 × 3.50	#70	63.50 × 2.50	70	20
LNE-DGJ-M-64	Φ64(70)	#70	75.50 × 3.75	#80	76.20 × 3.20	85	10
LNE-DGJ-M-75	Φ75(80)	#80	88.50 × 4.00			100	5
LNE-DGJ-M-100	Φ100	#100	114.0 × 4.00			125	5
LNE-DGJ-M-125	Φ125	#125	140.0 × 4.00			150	5
LNE-DGJ-M-150	Φ150	#150	165.0 × 4.50			180	5

